

USING DEPARTMENT:	Water Utility	ISSUED: 01/02/96	REVIEWED: 01/01/10	REVISED: 01/01/10
PREPARED BY:	Bill Flynn, P.E.	CITY STO	CK NUMBER:	
DESCRIPTION:	Type PVC1120. Be ASTM D 2672. Pij addition to the man intervals of 5 feet of includes POTABL permanent black m detectable warning below top of subgr	ell ends of pipe shall be be is approved for use in king required by ASTM or less, or the pipe shall b E, that word shall be obl parker. Abrasive methods tapes shall be installed: ade in paved areas or fin	diameter, meeting ASTM D 178 for solvent cement joints having small diameter force mains on D 1785, the pipe shall be mark be green to designate wastewate iterated by black spray paint suis shall not be used to obliterate 1 one 12" above the top of pipe a ished ground surface in unpave uried non-potable water line" at	g dimensions given in a case-by-case basis. In ed NON-POTABLE at er. If the pipe marking itable for burial or by POTABLE. Two and the other 12"- 18" d areas. The detectable

LISTING DATE	MANUFACTURER	PRODUCT IDENTIFICATION/COMMENT	APPROVAL
01/01/10	IPEX, INC. 10100 Rodney Street Pineville, NC 28134	XIRTEC 140 Must meet above	R. Lamb

NOTE: